

TECHNICAL DATA



TNT 500 W - 250 W

LITHIUM BATTERY
48 V / 499 Wh - 36 V / 468 Wh



VELOCIFERO

TECHNICAL DATA TNT 500 W - 250 W



COLORS:

PERFORMANCE INDEX	ITEM	TECHNICAL SPECIFICATIONS
DIMENSIONS	LxWxH(mm)	1698x644x1228
PRODUCT WEIGHT	Vehicle weight in running order(with battery)	23 Kg (36V) 25 Kg (48V)
	Maximum Load	120 Kg
CYCLING REQUIREMENTS	Suitable height	160-200 cm
	Full speed	50 Km/h
VEHICLE PARAMETERS	Maximum distance with one charge	35 Km (36V) 50 Km (48V)
	Working temperature	-5-45 degree celcius
BATTERY	Storage temperature	-5-45 degree celcius
	Rated Volt	36V 48V
MOTOR	Battery capacity	468 Wh 499 Wh
	Rated power	250 W 500 W
CHARGER	Rated Volt	36 V 48 V
	Torque	35 Nm 80 Nm
LIGHT	Input voltage	100-240 VAC
	Rated output Voltage	42 V 54.6 V
DISPLAY	Rated current	4 A 3 A
	Charging time	3-4 hours
TRANSMISSION SYSTEM	Headlight	LED
CHAIN	Tail light	LED
HANDLEBAR	Type	LCD
	Materials	Shimano(7speed)
DISC SIZE	Front	52T
	Rear	AL6061
TIRE	Front	Hydraulic disc brake, Φ203
	Rear	Hydraulic disc brake, Φ180
FRAME	Materials	Aluminium

E. CLASSIC 350 W

LITHIUM BATTERY
36 V / 432 Wh



VELOCIFERO

TECHNICAL DATA E.CLASSIC 350 W



COLORS:

PERFORMANCE INDEX	ITEM	TECHNICAL SPECIFICATIONS
DIMENSIONS	LxWxH(mm)	2080x720x1080
	SEAT HIGH(mm)	840
PRODUCT WEIGHT	Vehicle weight in running order(with battery)	33 Kg
	Maximum Load	120 Kg
CYCLING REQUIREMENTS	Applicable age	≥16 years old
	Suitable height	160-200 cm
VEHICLE PARAMETERS	Full speed	25 Km/h
	Maximum distance with one charge	80 Km
BATTERY	Maximum climbing angle	15%
	Working temperature	-5-45 degree celcius
MOTOR	Storage temperature	-5-45 degree celcius
	Rated Volt	36V
CHARGER	Battery capacity	432Wh
	Charging Voltage	42V
SPEEDOMETER	Weight	2.5 Kg
	Front	Spring shock absorber
SUSPENSION	Rated power	350W
	Rear	Mechanical disc, Φ180
BRAKE	Rated Volt	36V
	Size	Drum brake
TIRE	Input voltage	100-240 V
	Materials	Alloy
FRAME	Rated output Voltage	42V
	Rated current	1.5 A
CERTIFICATE	Charging time	7-8hours
	Type	LCD