

TECHNICAL DATA



OLIVER 3000 W **ELECTRIC** 2 SWAPPABLE LITHIUM BATTERIES 72 V / 2880 Wh



VELOCIFERO

TECHNICAL DATA **OLIVER 3000 W**



COLORS:

PERFORMANCE INDEX	ITEM	TECHNICAL SPECIFICATIONS
DIMENSIONS	LxWxH(mm)	1857x743x1386
PRODUCT WEIGHT	Vehicle weight in running order(with battery)	102 Kg
VEHICLE PARAMETERS	Working temperature	-5-45 degree celcius
	Storage temperature	-5-45 degree celcius
BATTERY	Rated Volt	72V
	Battery capacity	2880 Wh
	Charging Voltage	84 V
	Weight	10 Kg*2
MOTOR	Rated power	3000 W
	Rated Volt	72 V
	Torque	Peak 175 Nm
	Maximum rotate speed	900 r/min
	Full speed	85 Km/h
	Maximum distance with one charge	85 Km
CHARGER	Input voltage	100-240 V
	Rated output Voltage	84 V
	Rated current	10 A
	Charging time	5 hours
LIGHT	Headlight	LED
	Tail light	LED
CONTROLLER	Rated Volt	72 V
	Limited current	80 A
SPEEDOMETER	Size	5 inch TFT
SUSPENSION	Front	Leading link fork with double hydraulic shock absorber
	Rear	Hydraulic mono shock absorber progressive cantilever system
WHEEL BASE		1340mm
SEAT HEIGHT		744mm
CLEARANCE FROM THE GROUND		160mm
BRAKE	Front	Hydraulic disc brake,Φ220
	Rear	Hydraulic disc brake,Φ220
TIRE	Front	Tubeless 12-4.00
	Rear	Tubeless 12-4.00
FRAME	Materials	High-tensile steel
CERTIFICATE		EEC / L1e-b / L3e-A1

TENNIS 3000 W **ELECTRIC** 2 SWAPPABLE LITHIUM BATTERIES 60 V / 2400 Wh



VELOCIFERO

TECHNICAL DATA **OLIVER 3000 W**



COLORS:

PERFORMANCE INDEX	ITEM	TECHNICAL SPECIFICATIONS
DIMENSIONS	LxWxH(mm)	1857x743x1386
PRODUCT WEIGHT	Vehicle weight in running order(with battery)	102 Kg
VEHICLE PARAMETERS	Working temperature	-5-45 degree celcius
	Storage temperature	-5-45 degree celcius
BATTERY	Rated Volt	72V
	Battery capacity	2880 Wh
	Charging Voltage	84 V
	Weight	10 Kg*2
MOTOR	Rated power	3000 W
	Rated Volt	72 V
	Torque	Peak 175 Nm
	Maximum rotate speed	900 r/min
	Full speed	85 Km/h
	Maximum distance with one charge	85 Km
CHARGER	Input voltage	100-240 V
	Rated output Voltage	84 V
	Rated current	10 A
	Charging time	5 hours
LIGHT	Headlight	LED
	Tail light	LED
CONTROLLER	Rated Volt	72 V
	Limited current	80 A
SPEEDOMETER	Size	5 inch TFT
SUSPENSION	Front	Leading link fork with double hydraulic shock absorber
	Rear	Hydraulic mono shock absorber progressive cantilever system
WHEEL BASE		1340mm
SEAT HEIGHT		744mm
CLEARANCE FROM THE GROUND		160mm
BRAKE	Front	Hydraulic disc brake,Φ220
	Rear	Hydraulic disc brake,Φ220
TIRE	Front	Tubeless 12-4.00
	Rear	Tubeless 12-4.00
FRAME	Materials	High-tensile steel
CERTIFICATE		EEC / L1e-b / L3e-A1

TENNIS 125 **GASOLINE** 125 C.C. 4 STROKE



VELOCIFERO

TECHNICAL DATA **TENNIS 125 4 STROKE**



COLORS:

PERFORMANCE INDEX	ITEM	TECHNICAL SPECIFICATIONS
ENGINE	Type	125CC 4 stroke
		Single cylinder/water- cooled engine
	Maximum net power and rotation speed	8.8Kw/8250rpm
	Maximum torque and rotation speed	11.4N·m/6500rpm
	Ignition type	CDI
	Compression ratio	95:01
SUSPENSION	Front	Telescopic hydraulic front fork
	Rear	Hydraulic mono shock absorber progressive cantilever system
SPEEDOMETER	Size	5 inch TFT
TIRE	Front	100/90-12
	Rear	100/90-12
FRAME	Materials	High-tensile steel
OIL SUPPLY SYSTEM		EPI
FUEL TANK CAPACITY		4L
FUEL CONSUMPTION		≤367g/kw·h
WHEEL BASE		1326mm
DIMENSIONS	LxWxH(mm)	1850x670x1115
PRODUCT WEIGHT	Vehicle weight in running order	108 Kg
SEAT HEIGHT		765mm
GROUND CLEARANCE		130mm
CERTIFICATE		EURO 5