

TECHNICAL DATA



TNT 250 W - 500 W

LITHIUM BATTERY 36 V / 468 Wh

LITHIUM BATTERY 48 V / 499 Wh



VELOCIFERO

TECHNICAL DATA TNT 500 W - 250 W



COLORS: 

PERFORMANCE INDEX	ITEM	TECHNICAL SPECIFICATIONS	
DIMENSIONS	LxWxH(mm)	1698x620x1195	
	Seat height(mm)	840	
PRODUCT WEIGHT	Vehicle weight in running order(with battery)	28 Kg	30 Kg
	Maximum Load	120 Kg	
CYCLING REQUIREMENTS	Full speed	50 Km/h	
	Maximum distance with one charge	35 Km (36V) 50 Km (48V)	
VEHICLE PARAMETERS	Working temperature	-5-45 degree celcius	
	Storage temperature	-5-45 degree celcius	
BATTERY	Rated Volt	36 V	48 V
	Battery capacity	468 Wh	499 Wh
MOTOR	Rated power	250 W	500 W
	Rated Volt	36 V	48 V
CHARGER	Torque	35 Nm	80 Nm
	Input voltage	100-240 VAC	
LIGHT	Rated output Voltage	42 V	54.6 V
	Rated current	4 A	3 A
DISPLAY	Charging time	3-4 hours	
	Headlight	LED	
TRANSMISSION SYSTEM	Tail light	LED	
	Type	LCD	
CHAIN	Shimano(7speed)		
	52T		
HANDLEBAR	Materials	AL6061	
	Front	Hydraulic disc brake, Φ203	
DISC SIZE	Rear	Hydraulic disc brake, Φ180	
	Front	20"4.0	
TIRE	Rear	20"4.0	
	Materials	Aluminium alloy	
FRAME	Materials	Aluminium alloy	

E-CLASSIC 350 W

LITHIUM BATTERY 36 V / 432 Wh



VELOCIFERO

TECHNICAL DATA E-CLASSIC 350 W



COLORS: 

PERFORMANCE INDEX	ITEM	TECHNICAL SPECIFICATIONS	
DIMENSIONS	LxWxH(mm)	2080x770x1040	
	Seat height(mm)	840	
PRODUCT WEIGHT	Vehicle weight in running order(with battery)	33 Kg	
	Maximum Load	120 Kg	
CYCLING REQUIREMENTS	Maximum speed	25 Km/h	
	Maximum distance with one charge	80 Km	
VEHICLE PARAMETERS	Maximum climbing angle	15%	
	Working temperature	-5-45 degree celcius	
BATTERY	Storage temperature	-5-45 degree celcius	
	Rated Volt	36 V	
MOTOR	Battery capacity	432 Wh	
	Charging Voltage	42 V	
CHARGER	Weight	2.5 Kg	
	Rated power	350 W	
LIGHT	Rated Volt	36 V	
	Headlight	LED	
CONTROLLER	Rated output Voltage	42 V	
	Rated current	1.5 A	
SPEEDOMETER	Charging time	7-8hours	
	Type	LCD	
SUSPENSION	Front	Spring shock absorber	
	Rear	Mechanical disc, Φ180	
BRAKE	Size	26x4.0	
	Materials	Alloy	
FRAME	Materials	Alloy	
	CERTIFICATE	EN15194	